

# Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP white Simon 500 Cima

REF. 50003089-030



## BASIC INFORMATION

### DESCRIPTION

To ensure high speed data transmission in the work area, the flat base plate of voice and data Simon 500 Cima, is the option indicated. With finishes in a simple intense tone White, with dust cover for 1 element (protection against ingress of dust or other elements) and with 2 RJ45 category 6 FPT, as a guarantee of speed and security in your network to the transmission of data. Compatible with Keystone and cabling ports 22-26 AWG, has clips for enclosures horizontal or vertical, it does not need adapter and opens the range of installation possibilities to adapt to the specific needs of each specific space. The simplicity and speed of assembly, it facilitates the integration of the set in a reduced space. Made of halogen-free, self-extinguishing thermoplastic prevents the flame spread and toxicity by smoke in case of fire.

### FINISH

White

### PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

### ETIM CLASS

EC000018

### COMPATIBILITY

Simon 500 Cima enclosures

### REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DUST PROTECTION

Yes

### PLATE TYPE

Flat

### CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

### FORMAT

RJ45

### RAL

9003

### RJ45 CONNECTION

Without insertion tool

### IP RATING

IP20

### RJ45 ADAPTOR MODULE

Included in voice and data plate

### CONNECTOR CHARACTERISTICS

category 6 FTP

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

### NUMBER OF CONNECTORS

2

### SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

### RJ45 CONNECTORS

Included in voice and data plate

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### VERSION

Single

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### NUMBER OF MODULES

1

## INSTALLATION AND MAINTENANCE

### REMOVAL OF CONNECTOR

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

### INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

### INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

### REMOVAL OF THE PLATE

Only with tool

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018\*1

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097885

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS  
WEIGHT

0.055

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.1

PRODUCT NET WEIGHT

0.055

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

