# Kit Flash 60 consisting of schuko power socket end in Quick-connection connector white Simon 400

REF. **43101002-130**



## BASIC INFORMATION

### DESCRIPTION

Kit based on schuko socket-outlet to be installed in furniture with an optional protective cover to allow for closure and conceal connections when not in use. This product is supplied in white finish, assembled and wired with a 20 cm long flexible cable ending in a male quick connect overhead connector of 3 poles type Wieland® GST8i with safety anchoring to facilitate safe connection and disconnection from the power network without the need to interrupt the power supply. The kit is supplied with the internal connections already made. It is only necessary to create the hole in the furniture where the product will be fasten and once done, connect it to the power supply to make it functional.

| FINISH | MATERIAL | ETIM CLASS |
| --- | --- | --- |
| White | Plastic | EC000125 |

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Protective lid available (as an option) to protect the socket-outlet against entry of dust and small objects

### RJ45 CONNECTORS
No

### CONNECTOR TYPE
Schuko

### NUMBER OF CONTACTS
3

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### CURRENT (A)
16 A

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### NOMINAL VOLTAGE (V~)
250 V~

### RAL
9003

### RECESS DIMENSION (MM)
ø54 mm

### RJ45 ADAPTOR MODULE
No

### SNAP-FIT RJ45 PLATES
No

### SNAP-FIT TYPE
No

### VOLTAGE (V~)
250 V~

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS
Only with tool

### REMOVAL OF CONNECTOR
No tools needed

### EXTINGUISHING (°C)
+650 °C (according to standard IEC 60670)

### REMOVAL OF THE FRAME
Only with tool

### SECURING POSSIBILITIES
Using supplied claws

### TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | IEC 60884-2-7 Ed 1.1*1 | UNE 20315-2-7:2008*1 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2*2 | UNE 20315-1-1:2017*2

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053292075

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING GROSS WEIGHT
0.136

### PRODUCT NET WEIGHT
0.124

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053292075

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
72

### PACKAGING WIDTH
72

### PACKAGING LENGTH
105

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
544320

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0.136

### PACKAGING NET WEIGHT
0.124

### PACKAGING WEIGHT UNIT
KGM