

Reduced depth floor box with 3 double elements for installation in technical or pavement floor gray Simon Cima

REF. SF300C/1



BASIC INFORMATION

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With mechanisms Simon Series S and Simon 25 / Simon K45 (via adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

6

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

790kg

NUMBER OF PRE-PUNCHED HOLES 55 X 20 MM

6

RAL

7011

RECESS DIMENSION (MM)

Ø 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

3

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050877

PRODUCT NET WEIGHT

2.03

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

8.45

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050877

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.02

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

80

PACKAGING NET WEIGHT

2.03

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

325

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.03

PACKAGING LENGTH

325