S-Video connector female with trim plate aluminium Simon K45

REF. **K103B/8**



BASIC INFORMATION

DESCRIPTION

Give the highest quality at the signal to connect your computer to the screen, with the S-Video female connector of the collection Simon K45 including a trim cover finished in Aluminium, the S-Video connector, K45, not only will ensure the best quality of video with image enhanced but sophistication of finishes that adapt perfectly to the set of the space. Composed of materials with thermoplastic isolated free of halogens, it inhibits the flame spread in case of fire and smoke. The connector reaches temperatures that vary the -25 and 50ºC. With screw terminal connection, it is suitable for its assembly in surface-mounted or flush-mounted, allowing a maximum length of 30 meters and cabling a cable section cross-section of 0.2 to 0.5 mm With a resolution of video standard and speed of 400 Megabit / second, the Simon K45 S-Video connector, female, is the hallmark of security and functionality in a single space.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Female S-Video connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
S-Video

NUMBER OF CONTACTS
4

NUMBER OF POSSIBLE ELEMENTS
1/2 element

FORMAT
S-Video

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
5

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436064683

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.025

PRODUCT NET WEIGHT
0.025

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436064683

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
42

PACKAGING LENGTH
50

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.012

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.025

PACKAGING NET WEIGHT
0.025

PACKAGING WEIGHT UNIT
KGM