

Angled voice and data plate with dust cover for 1 element with 2 RJ45 category 6 UTP aluminium Simon 500 Cima

REF. 50002086-033



BASIC INFORMATION

DESCRIPTION

Plate for voice and data tilted plate of the Simon 500 Cima and available in aluminium colour. It is a plate with dust cover and 1 element with 1 RJ45 category 6A FTP of Keystone I, II, ATT ® / Avaya ® and that has been designed in accordance with the TIA 568 C. 2. It measures 50 x 50 x 42,5 mm and is compatible with cabling 22-26 AWG and has been manufactured with metal components with halogen-free thermoplastic insulation and autoextinguishible. This material is very safe and provides a low toxicity in case of fire and also that does not cause the fire, if it is producing a fire in the place where it is installed, the plate. The plate for voice and data of the range of Simon 500 Cima can be used in public places with temperatures between -5 and the most of 60 ° C and includes all the clips necessary to set it in enclosures horizontal or vertical, without that you have to use any adapter for this task. To clean it, use only a soft, dry cloth and will be perfect.

FINISH

Aluminium

PACKAGING CONTENTS

Angled voice and data plate with dust cover, 2 category 6 UTP RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6 UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097632

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.079

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.58

PRODUCT NET WEIGHT

0.079

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

