

2-way switch for card with 1 micro switch and light indicator 250V~ grey Simon 75

REF. 75526-35



BASIC INFORMATION

DESCRIPTION

2-way switch for card with 1 microswitch and indicator light has a current of 6 A and a voltage of 250 V~, comes in grey colour, it belongs to the wide and extensive range of products of the Simon 75 brand. Fast terminal connection and works with card. It is recommended the installation combined with a contactor / relay. If this is not the case, the maximum current of the 2-way switch is 6° (inductive 2A), it is very important when position, place the frame to know that the tabs of the same. It has a signal function with a consumption of 1 mA, for its installation it will suffice to apply pressure or place on the surface, the wire is 0.5 mm, the material of manufacture is to socket of metal components with halogen-free insulation and thermoplastic trims that are designed to reach temperatures that can oscillate without any inconvenience between 5 and 40°, and can support up to a maximum of between -25 and 50° C. Complies with the regulation UNE-EN 60669-1: 1996 + 60669-2-1: 2002 + 60669-2-3: 1999. For hygiene, clean with a soft, dry cloth, do not use abrasive cloths and / or abrasive cleaners containing chlorine.

FINISH

Grey

PACKAGING CONTENTS

Mechanism and cover

COMPATIBILITY

Simon 75 frames

ETIM CLASS

EC001590

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

POWER SUPPLY (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.08

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3017190

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053017968

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.4

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.4

UNITARY PACKAGING GROSS
WEIGHT

0.08

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223