IP66 mechanism holder unit with safety lock and a French socket base with 1RJ45 category 5e UTP stainless steel Simon K45

REF. **KSE25USEC/23/72**

BASIC INFORMATION

DESCRIPTION

With the range update, its equivalent for the new version is the KFH125USEC/72 reference.

FINISH

Stainless steel

MATERIAL

Stainless steel

ETIM CLASS

EC000024

TECHNICAL INFORMATION

DUST SHUTTER
No

FORMAT
French

HEAT RESISTANCE (ºC)
+70ºC (according to standard IEC 60670)

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP66

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1000kg

RECESS DIMENSION (MM)
145 x 145 mm en falso suelo

VOLTAGE (V~)
250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
12

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+650 ºC (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY
Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436063884

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.46

PRODUCT NET WEIGHT
0.46

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436063884

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
77

PACKAGING WIDTH
137

PACKAGING LENGTH
137

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.445

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.46

PACKAGING NET WEIGHT
0.46

PACKAGING WEIGHT UNIT
KGM