

Metal mini-tower 4 heights and 1 side for 8 elements stainless steel Simon K45

REF. KT0800/8



BASIC INFORMATION

DESCRIPTION

It is characterized by a metal mini-tower 4 heights, 1 side and suitable for 8 elements. It is made in stainless steel and is included in the Simon 27 series, a collection that represents a clear commitment to connectivity solutions to all types of spaces. The article measures 298,5 x 221 x 68 mm and consists of 4 double modules. It is in compliance with current regulations and is suitable for installing on any floor type, whether raised or concrete flooring. The racks have linkable parts that make blocks, allowing separation of the electrical part of the part of voice and data, making it easier, in this way, the maintenance. It does not require much effort and it is sufficient to use a soft and dry suede. We do not recommend the use of abrasive cleaners containing chlorine, as they could damage the product.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC001941

MATERIAL

Stainless steel

PACKAGING CONTENTS

Metal mini-tower, protective foam, metal separator, ground connection cable, screws and installation manual

REMARKS

The centre frames include linkable parts that make blocks, allowing separate the electrical part of the part of voice and data for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam between the fastening base and mini-tower structure.

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

EARTHING RESISTANCE

< 0.05 Ω

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Guaranteed through the installation of the metal separator in the housing fitted into the mini-tower for this purpose.

HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MΩ to 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 120° C

NUMBER OF MODULES

4 double modules

VERSION

1-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using supplied screws

REMOVAL OF THE FRAME

Only with tool

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053092651

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.154

PRODUCT NET WEIGHT

2.154

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053092651

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

67

PACKAGING WIDTH

168

PACKAGING LENGTH

398

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4.48

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.154

PACKAGING WEIGHT UNIT

KGM