

Customisable set with 1 schuko socket outlet and 5 empty elements black S400 Top

REF. 42601000-138



BASIC INFORMATION

DESCRIPTION

With the kit of desk top customizable of the collection Simon 400 Top, you will get the maximum functionality of its devices connected in the minimum space compact. With a design of simple lines and finishes in black, this kit consists of 1 Schuko socket-outlet and 5 empty elements for that includes the application-specific functions that requires the room. Ideal for working areas, the kit is designed for flush installation, fitted with clamps pages, and has a size of 295 x 120 x 80 mm Compatible with a voltage of 250 V and current of 16 A, its dielectric strength is 2000 V at 50H per minute and has a insulation resistance > 5 M Ω at 500 V. This kit is connected to a figure Wieland gst 18i with 3-pole male in-line and patch cord of 22 cm. Made of anodised aluminium and thermoplastic self-extinguishing halogen-free, protects the room in case of fire and prevents the flame spread and toxicity by smoke.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

5

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF REAR ENTRANCES

5

NUMBER OF SOCKETS

1 socket for standard current circuit

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196007

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.835

PRODUCT NET WEIGHT

0.835

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196007

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

330

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.835

PACKAGING WEIGHT UNIT

KGM