

Adjustable recessed box with 2 elements for installation on false floor graphite Simon K45

REF. KF210/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

2

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

800kg

RAL

7021

RECESS DIMENSION (MM)

170 x 115 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS

2

REMOVAL OF COVER

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053125311

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053125311

PACKAGING VOLUME

2871375

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

95

PACKAGING GROSS WEIGHT

0.76

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

155

PACKAGING NET WEIGHT

0.76

UNITARY PACKAGING GROSS
WEIGHT

0.76

PACKAGING LENGTH

195

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.76