

Satellite socket single F type female with trim plate aluminium Simon K45

REF. K102C/8



BASIC INFORMATION

DESCRIPTION

If you are looking for security, innovation and functionality in its satellite socket, Simon K45 is what you need. With trim cover, finished in Aluminium and connection by welding, the single F type satellite Simon K 45, it is designed to maximize the effectiveness and security of their room. Composed of halogen-free thermoplastic materials, it provides security against fire to prevent the flame spread and toxicity by smoke and, in addition, reaching temperatures of between -25 and 50°C. Designed for installation both recessed and surface-mounted, it accepts a maximum length of cabling 90 metres (RG-6 type) and cable section of 6-8mm. Thanks to its trim cover, its finishes in Aluminium, and the guarantee of security and high performance of all the collection Simon K45, the SAT single F type, it fits perfectly into the space, maximizing the features and possibilities of connection appropriate to each need.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Simple F type female satellite socket

ETIM CLASS

EC000439

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 6 to 8 mm

CONNECTOR TYPE

SAT

NUMBER OF CONTACTS

1

NUMBER OF POSSIBLE ELEMENTS

1/2 element

FORMAT

SAT

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

1

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 + A1:2015 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.136

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046665

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

91140

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

1.36

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

1.36

UNITARY PACKAGING GROSS
WEIGHT

0.136

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140