

Modular Luminaire 730 120x10 4000 K General 1-10 V

REF. 73062140-884



BASIC INFORMATION

DESCRIPTION

Simon presents its new modular luminaire with Art. No. 73062140-884, a solution for those who want to illuminate a working area with a neutral colour tone NW. Perfect for general lighting with a Colour Rendering Index of 80, this luminaire also has a great relationship lm/watt.

With dimensions of 120x10 centimetres, its installation is in false ceiling. It has finishes in white colour and allows the total control of the intensity of light thanks to its 1-10 V system.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LUMENS (LM)

3400 lm

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS/W

3400lm/ 34,5W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100.000 h at 25°C

OPTICS

General

POWER SUPPLY (V~)

230 V~

L90 (°C)

50.000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

100°

POWER (W)

34.5 W

CONTROL

1-10 V

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

99 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted, Concealed ceiling, Semi-concealed ceiling, Flush-mounted

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053204375

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

3.1

PRODUCT NET WEIGHT

2.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053204375

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

87

PACKAGING WIDTH

110

PACKAGING LENGTH

1215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

11627550

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3.1

PACKAGING NET WEIGHT

2.8

PACKAGING WEIGHT UNIT

KGM