

Metal surface mount wall box kit 4 double elements with 1 double socket, 2 dual UPS and 2 plates 2 RJ45 graphite

Simon 500 Cima

REF. 51001401-036



BASIC INFORMATION

FINISH

Stainless steel

MATERIAL

Stainless steel

PACKAGING CONTENTS

Surface-mounted wall kit, metal
partition wall, ground
connection cable and installation
manual

ETIM CLASS

EC002600

REMARKS

The frame holders include linkable parts that form blocks, allowing the electrical part to be separated from the voice and data part for ease of maintenance

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Standard 110, SL110, SL Tool-less, 216000 and 216005, Brand-Rex®, ADC Krone® KM8 Keystone, BeldenCDT® Giga Flex Keystone, Ersys®, General Cable®, Molex®, Panduit® Netkey, Ortronics® Clarity TechChoice Keystone, Rit® and other manufacturers with Keystone snap-fit system.

NUMBER OF CONNECTORS

4

RJ45 CONNECTORS

Not included

DUST SHUTTER

Yes

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the rail fitted into the box for this purpose.

FORMAT

Schuko

NUMBER OF ENCLOSURES FOR GROUND CONNECTION

Dedicated rail in the box structure

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP20

LED CONSUMPTION INDICATOR (mA)

0.55

LINKABLE

Yes, using accessory included 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

8

MONOBLOCK

Yes

NUMBER OF PLATES

2 voice and data plates

PLATE TYPE

Flat

NUMBER OF PRE-PUNCHED HOLES 43 X 43 MM

2

RJ45 ADAPTOR MODULE

Included in voice and data plates

NUMBER OF SIDE ENTRANCES

Upon request

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, Keystone II and Systimax

NUMBER OF SOCKETS

1 double socket for standard current circuit and 2 double sockets for stable current circuits

VERSION

4 double elements

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

REMOVAL OF THE FRAME

Only with tool

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface-mount wall installation

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053100844

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053100844

PACKAGING VOLUME

3.062

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

67

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

168

PACKAGING NET WEIGHT

2.1

UNITARY PACKAGING GROSS
WEIGHT

2.1

PACKAGING LENGTH

272

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.1

