

French socket outlet 16A 250V~ with safety device and screw terminal connection white Simon 27 Play

REF. 27458-35



BASIC INFORMATION

DESCRIPTION

This switch for element of up to 16 A and 250 volts, it is part of the range Simon K45. The device with indicator light function and comes with trim plate in white colour. Simon products are looking for a high functionality but goes further, and are converted to decorative elements. By there is a wide range of colours and finishes that will that adapt perfectly in any room, maintaining the harmony appearance of this. In this sense, the white finish is ideal for any room. The indicator light function of the product will bring modernity to the final set. The rocker operation of the switch is very simple and interactive. It measures 45 x 45 millimetres and is made up of two modules that is very simple installation by means of flush mounting or surface mounting. It has a technical Faston / Welding terminal connection. It stands out for the quality of its thermoplastic trim and that are its metal components with insulation, halogen-free.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

MONOBLOCK

No

CABLE SECTION ADMITTED (MM)

2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

French

TYPE OF MECHANISM

Insertion

VERSION

Single

INDICATOR FUNCTION

No

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.052

PRODUCT NET WEIGHT

0.052

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053024904

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

52

PACKAGING WIDTH

105

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1201200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.52

PACKAGING NET WEIGHT

0.52

PACKAGING WEIGHT UNIT

KGM