

Flat voice and data plate with dust cover for 1 element with 2 category 5e UTP RJ45 graphite Simon 500 Cima

REF. 50004089-038



BASIC INFORMATION

DESCRIPTION

Increase the speed of the transmission of data on the work area, thanks to the flat base plate of voice and data of the collection Simon 500 Cima. With dust cover for an element and 2 RJ45 category 5e UTP, guarantees maximum functionality in a reduced space. With discreet yet elegant finishes in Graphite, the flat base plate 500 Cima integrates seamlessly into the specific space, adapting to the specific needs of each room to be suitable for assembly in enclosures horizontal or vertical thanks to its direct snap-fit and without the need of adapters. It is also compatible with Keystone-type ports, cabling 22-26 AWG and with all kinds of voice and data connectors (RJ45) on the market. Made of halogen-free thermoplastic, prevents the flame spread and toxicity by smoke in case of fire, reaching to reach a temperature range of installation of -5°C and more than 60 ° C

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 category 5e UTP RJ45 and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097939

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.035

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.7

PRODUCT NET WEIGHT

0.035

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

