

**Mechanism-holder unit IP66 with manual lock and Schuko
socket outlet with 1 RJ45 category 6 UTP stainless steel
Simon K45**

REF. KSE16U/23/72



BASIC INFORMATION

DESCRIPTION

It is a mechanism-holder unit unit with manual closure and type Schuko socket outlet with 1 RJ45 category 6 UTP. This article is made of AISI 304 stainless steel, while the baseboard is self-extinguishing thermoplastic and halogen-free, a material highly secure in the event of a fire. The product has dimensions of 130 x 130 x 55 mm and is included in the Simon 27 series. Its design allows incorporation in any type of floor, both in raised or concrete floor floor, and by combining the mechanism-holders unit with the tray appropriate to the type of installation (reference KGE170 for concrete floor, and reference KGE170TF for raised floor). Also, the cover has anchor points that protecting the connections pressures and stresses produced by the traffic of people during its use. For the maintenance of this mechanism-holder unit, use a soft and dry cloth. With the range update, its equivalent for the new version is the KFH116U/72 reference.

FINISH

Stainless steel

PACKAGING CONTENTS

IP66 brass mechanism-holder unit with manual lock, square sealing gasket for IP66 tray, 1 Schuko socket base, 1 category 5e RJ45 UTP connector, 4 screws for fastening the mechanism-holder unit and installation manual

ETIM CLASS

EC000024

MATERIAL

Stainless steel

REMARKS

The cover has anchor points that protect the connections during use against pressures and stresses due to the passage of personnel.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, when the mechanism-holder unit is not in use, the cover can be hermetically sealed.

AVAILABLE IN

Empty IP66 brass mechanism-holder unit to complete with solutions from the K45 range, with socket plug and housing for an RJ45 connector, and combination of a socket plug with RJ45 connector

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal (1 input / 1 output)

NUMBER OF CONNECTORS

1

RJ45 CONNECTORS

Includes 1 RJ45 category 6 UTP connector

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

DUST SHUTTER

No

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07,08

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

CURRENT (A)

16 A

IP RATING

IP66

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1000kg

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2 modules

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

RJ45 ADAPTOR MODULE

Included with the mechanism-holder unit

SNAP-FIT RJ45 PLATES

Keystone I and II

SNAP-FIT TYPE

Keystone I and II

NUMBER OF SOCKETS

1 socket for standard current circuits

VERSION

1 element

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

The mechanism-holder unit is fitted to the tray using 4 x 2.5 mm hexagonal head screws (Allen type) supplied with the mechanism-holder unit.

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

The cover opens in the direction chosen according to the orientation of the tray during the installation phase.

INSTALLATION TYPE

Its design allows incorporation in any type of floor, be it a raised or a concrete floor, combining the mechanism-holder unit with the tray in accordance with the type of installation (ref. KGE170 for concrete floor, and ref. KGE170TF for raised floor)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF TERMINALS

3 inputs / outputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056046

PRODUCT NET WEIGHT

0.445

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1445213

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436056046

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.445

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

77

PACKAGING NET WEIGHT

0.445

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

137

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.445

PACKAGING LENGTH

137