


Kit Flash 90 consisting of israelian modular power socket, USB charger Type C 20W and housing for Keystone connector white Simon K45

REF. KR3330013/9



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular israelian power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and conceal the connections when not in use. Includes a 20W USB Type-C charger and a housing for a Keystone jack connector in white finish. Supplied with a 20cm long patch cable terminated with a 3-pole Wieland® Gst18i male quick-connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to cut the die in the furniture where the product will be mounted and, once completed, connect it to the mains for operation.

FINISH

White

MATERIAL

Plastic

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

Israeli

SNAP-FIT RJ45 PLATES

Directly to the trim cover

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

CURRENT (A)

16 A

SNAP-FIT TYPE

Keystone

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

IP RATING

IP20

USB CHARACTERISTICS

Charging

RJ45 CONNECTORS

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CURRENT (A)

2,2 A

CONNECTOR TYPE

Israeli

NOMINAL VOLTAGE (V~)

250 V~

POWER DELIVERY USB

Yes

RAL

9003

QUICK CHARGE USB

Yes

NUMBER OF CONTACTS

3

RECESS DIMENSION (MM)

ø80 mm

USB VOLTAGE (V~)

9 V~

DUST SHUTTER

No

RJ45 ADAPTOR MODULE

Yes

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

No tools needed

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 | Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053398210

UNITARY PACKAGING GROSS WEIGHT

0.736

PACKAGING LENGTH

252

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.576

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3931200

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053398210

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.736

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

120

PACKAGING NET WEIGHT

0.576

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM