

# Neutral push-button switch 10A 230V~ with slender rocker and fast terminal connection system gold Simon 270

REF. 20001150-095



## BASIC INFORMATION

### DESCRIPTION

Discover the Simon iO blinds switch with slender rocker 700 VA bronze Simon 270 from the Simon 270 series. A product designed to deliver functionality, compatibility and style for residential and commercial installations.

### FINISH

Gold

### MATERIAL

Plastic

### PACKAGING CONTENTS

Mechanism, cover and instruction sheet

### TYPE OF ROCKER

Slender

### COMPATIBILITY

Simon 270 frames

### ETIM CLASS

EC000029

### SYMBOL

Arrow,Star,On-off

## TECHNICAL INFORMATION

|                                                   |                                                                                                                     |                                                  |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| AVAILABLE MARKET<br>CE                            | CURRENT (A)<br>10 A                                                                                                 | OPERATING TEMPERATURE<br>RANGE (°C)<br>5 - 45 °C |
| CABLE SECTION ADMITTED (MM)<br>From 1,5 to 2,5 mm | IP RATING<br>IP20                                                                                                   | POWER SUPPLY (V~)<br>230 V~                      |
| NUMBER OF POSSIBLE<br>ELEMENTS<br>1 element       | MAINTENANCE<br>Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | RAL<br>1036                                      |
| FORMAT<br>Push-button                             | TYPE OF MECHANISM<br>Pivoting                                                                                       | STORAGE TEMPERATURE RANGE (°C)<br>-25 - 75 °C    |
| FREQUENCY<br>50 - 60 Hz                           | NOMINAL VOLTAGE (V~)<br>230 V~                                                                                      | VOLTAGE (V~)<br>230 V~                           |
| INDICATOR FUNCTION<br>No                          |                                                                                                                     |                                                  |

## INSTALLATION AND MAINTENANCE

|                                     |                                                         |                                                     |
|-------------------------------------|---------------------------------------------------------|-----------------------------------------------------|
| CABLE STRIPPING NECESSARY (MM)<br>7 | INSTALLABLE IN FLUSH MOUNT<br>JUNCTION BOX<br>Universal | INSTALLATION TYPE<br>Suitable for flush mounting    |
|                                     | INSTALLATION DIRECTION<br>Horizontal, Vertical          | TYPE OF TERMINAL<br>CONNECTION - FUNCTION 1<br>Fast |

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053268766

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.02

### PRODUCT NET WEIGHT

0.02

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053268773

### UNITS CONTAINED PACKAGING

10

### PACKAGING HEIGHT

47.75

### PACKAGING WIDTH

57

### PACKAGING LENGTH

262

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

713098.5

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.2

### PACKAGING WEIGHT UNIT

GRM

