

Depth expander 4 double elements for surface mount or flush-mount wall box white Simon 500 Cima

REF. 51030904-030



BASIC INFORMATION

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using specific adaptors), combinable with the Simon Trunking range

PACKAGING CONTENTS

Depth expander, metal partition wall and installation manual

ETIM CLASS

EC002328

REMARKS

The depth expander ensures the perfect fit of all categories of RJ45 connectors on the market in combination with flat voice and data plates.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

3 and 4 double elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the selected wall enclosure.

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

8

RAL

9003

RECESS DIMENSION (MM)

141 x 262 mm (* para instalação encastrada na parede)

VERSION

4 double elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using the screws supplied

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Suitable for flush mounting or surface mounting onto wall in combination with the corresponding enclosure

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053092217

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.328

PRODUCT NET WEIGHT

0.328

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053092217

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

50

PACKAGING WIDTH

165

PACKAGING LENGTH

285

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2.351

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.328

PACKAGING WEIGHT UNIT

KGM

