

Front kit for 1 element with 1 Simon iO dimmer switch matt black Simon 100

REF. 10020114-238



BASIC INFORMATION

DESCRIPTION

Front kit for 1 element with 1 adjustable switch Simon iO made in elegant black colour with a nice matte finish. This device is part of the Simon 100 series and, therefore, is compatible with all the mechanisms of that series.

The voltage capacity of this kit will be 250V. It is a standard product designed to be marketed throughout the EC. For its preparation, it complies with directive 2014/35/UE LVD + directive 2014/30/UE EMC + directive 2011/65/UE RoHS + EN 50581: 2012 + EN 60669-2-1: 2004 + have been followed EN 60669-2-1: 2004 A1: 2009 + EN 60669-2-1: 2004 A12: 2010.

Its emborning is cut-based and it operates by push-button. It works with an intensity of 10 AX.

This kit has dimensions of 85.5x83.5mm and can be installed both vertically and horizontally.

For a good maintenance just use a soft cloth in soapy water, thus avoiding abrasive cleaners containing chlorine. The interval for the temperature of its proper functioning shall be from 5° C to 40° C and its storage temperature must be in the range -25° C to 50° C.

FINISH

Matt black

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

10 AX

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Push button rocker switch/Insertion

MONOBLOCK

No

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

1 element

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION DIRECTION

Horizontal, Vertical

KIT INSTALLATION DIRECTION

Vertical and horizontal

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

1 click connection (1 click®)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-1:2004 + EN 60669-2-1:2004 A1:2009 + EN 60669-2-1:2004 A12:2010

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053213254

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.064

PRODUCT NET WEIGHT

0.064

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053213254

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

10

PACKAGING WIDTH

84

PACKAGING LENGTH

84

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

70560

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.064

PACKAGING WEIGHT UNIT

KGM