Downlight 703.23 Round Orientable 2700 K Spot DALI White

REF. **70323330-282**



BASIC INFORMATION

APPLICATION

Hotel,Restaurants,Residential,Retail,Office,Healthcare,Education

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (°C)
15 - 35 °C

POWER SUPPLY (V~)
100/240 V~

COLOR TEMPERATURE (K)
2700 K

CONTROL
DALI

CRI
80

CUT OFF
Yes

DRIVER INCLUDED
Yes

L70 (°C)
30,000 h at 25 °C

LIGHT BEAM APERTURE ANGLE (°)
20°

LIGHTING EFFICIENCY (LM/W)
94 lm/W

LUMENS (LM)
700 lm

LUMENS/W
700 lm/7.5 W

OPTICS
Spot

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
7.5 W

SERVICE LIFE
30.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053088913

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.401

PRODUCT NET WEIGHT
0.28

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053088913

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.31

PACKAGING NET WEIGHT
0.28

PACKAGING WEIGHT UNIT
KGM