

Wall luminaire Spot Duo BT Mesh 15W with detector 10m PIR+LUX anthracite IP44 3Y

REF. 89395602-763



BASIC INFORMATION

DESCRIPTION

Wall-mounted apply with PIR detector and Bluetooth connectivity. The power is 16 W, the luminous flux is 1024 lm, and the color temperature is 3000 K. The maximum installation height is 4m, and the installation is on wall (surface). The detection range is 10 mm, and the detection angle is 90 °. The brightness regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The luminaire configuration is done through a Bluetooth application. Possibility of interconnection between luminaires through Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection degree IP 44 and IK 03, and dimensions: 175 x 97 x 98 mm. 3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Anthracite

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400487

UNITARY PACKAGING GROSS WEIGHT

1.295

PACKAGING LENGTH

275

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.997

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400487

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.295

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

125

PACKAGING NET WEIGHT

0.997

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

225

PACKAGING WEIGHT UNIT

KGM