

Luminaire HOLE 110 Trimless 3000K Flood White CRI98

REF. 91422932-300



BASIC INFORMATION

FINISH

White

APPLICATION

Trimless

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

98

LUMENS (LM)

700 lm

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS/W

700

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

33 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

RAL

9016

L90 (°C)

40.000h at 25°C

POWER (W)

9 W

COLOR TEMPERATURE (K)

4000 K

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547068524

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547068524

PACKAGING VOLUME

13545000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

180

PACKAGING GROSS WEIGHT

1.7

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

215

PACKAGING NET WEIGHT

1.58

UNITARY PACKAGING GROSS
WEIGHT

1.7

PACKAGING LENGTH

350

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.58