

Waterproof linear luminaire BT Mesh 42W 1800K with detector 10m HF+LUX IP65

REF. 89392600-421



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and Bluetooth connectivity. The power is 42.4 W, the luminous flux is 5940 lm, and the color temperature is 1800 K.

The maximum installation height is 4m, and the installation is surface-mounted. The detection range is 10m, and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux, and the time setting range is 5 s - 60 min.

The luminaire configuration is done through a Bluetooth application. Possibility of interconnection between luminaires through Bluetooth mesh.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Protection rating IP 65 and IK 07 and dimensions: 1500 x 87 x 58 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#).

FINISH

White

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP65

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

07

OPERATING TEMPERATURE RANGE (°C)

-20...+40

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440094

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2.2

PRODUCT NET WEIGHT

1.77

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440094

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

100

PACKAGING LENGTH

1690

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

2.2

PACKAGING NET WEIGHT

1.77

PACKAGING WEIGHT UNIT

KGM