Fastening bracket for Teleblock telescopic profiles with automatic elevation Simon K45

REF. **KTLA7**



BASIC INFORMATION

DESCRIPTION

The fastening bracket for telescopic profiles with automatic elevation Teleblock is available in black finishes and is part of the wide catalogue of solutions of the series Simon K45. With dimensions of 108x101 mm and has been made with thermoplastic components and self-extinguishing halogen-free to ensure that they do not spread flames in case of fire, along with very low toxicity in case of smoke emissions. The exclusive series Simon K45 has been specially created to offer products of great quality and security. For this reason, we use materials of the best quality and resistance, to make your home in a site safer. Because at Simon, we innovate so that our mechanisms and solutions remain at the standard of our customers.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Fastening bracket for telescopic profiles with manual elevation and installation manual.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

RAL
7021

RECESS DIMENSION (MM)
Ø 114 mm

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening the fastening thread supplied with the Simon K45 Teleblock telescopic profile. Note: this article is a replacement part and is supplied with the Simon K45 Teleblock telescopic profile.

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053090886

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.263

PRODUCT NET WEIGHT
0.263

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053090886

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
165

PACKAGING WIDTH
130

PACKAGING LENGTH
150

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3.217

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.263

PACKAGING WEIGHT UNIT
KGM