USB charger type A+C port 65W PowerDelivery and QuickCharge black Simon K45

REF. **K126H/14**



BASIC INFORMATION

DESCRIPTION

With dimensions of 45 x 45 mm, the K126H/14 charging base has two USB type A+C ports in black. The dual module allows simultaneous charging of 2 devices with 65W power using Power Delivery and Quick Charge 3.0 technology, enough to maintain the charge of our portable devices. But the best part, without a doubt, is its construction with metallic components coated with self-extinguishing thermoplastic insulation and halogen-free materials, ensuring that flames do not spread in case of fire, as well as having low toxicity in the event of smoke emission. The Simon K45 collection offers suitable solutions even for the most demanding users, thanks to our commitment to innovation and the use of the highest quality materials.

FINISH

Graphite

MATERIAL

Thermoplastic

COMPATIBILITY

K45 Solutions. Solutions 500 Cima through adapter 50012088-038.

ETIM CLASS

EC002949

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

NUMBER OF CONNECTORS
2

CONNECTOR TYPE
USB A + USB C

NUMBER OF CONTACTS
2

FORMAT
USB A + USB C

INDICATOR FUNCTION
Yes

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
230 V~

PLATE TYPE
Flat

POWER SUPPLY (V~)
230 V~

RAL
9005

RECESS DIMENSION (MM)
48

USB CHARACTERISTICS
PD QC 65W

POWER DELIVERY USB
Yes

QUICK CHARGE USB
Yes

NUMBER OF WIRES
2

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
8

REMOVAL OF CONNECTOR
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION
Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

TYPE OF TERMINAL CONNECTION - FUNCTION 2
Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024 | EN 50563:2011 + A1:2013 | EN 61000-3-3:2013 + A1:2019 + A2:2021 EN IEC 62368-1:2020 + A11:2020 | EN 50563:2011 + A1:2013 | EN IEC 61000-6-1:2019 | EN IEC 63000:2018 | EN IEC 61000-6-3:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053329276

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.103

PRODUCT NET WEIGHT
0.103

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053329276

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
65

PACKAGING WIDTH
55

PACKAGING LENGTH
65

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
232375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.121

PACKAGING NET WEIGHT
0.103

PACKAGING WEIGHT UNIT
KGM