

Modular luminaire 726 60x60 NW

REF. 72660033-884



BASIC INFORMATION

DESCRIPTION

Modular luminaire 60 x 60 lights with LED neutral colour (NW). It is a product category B and is part of the series of modular luminaires Simon 726 Opal and optics. It is the temperature of the colour of the luminaire is 4000 K. It has 3200 lumens to 39 W power. Requires a power supply of 220-240 V and has a frequency of 50-60 Hz. The electric control of this luminaire Simon is performed by the classic system of ON-OFF. This provides a very long its use, converting it in a product functional and practical. Its dimensions are 595 millimetres and the total weight of the luminaire is 2,6 kilos. This luminaire is presented in a beautiful and stylish finished in aluminium. Thanks to this can be integrated into any room, keeping a unique appearance. The installation is carried out in false ceiling, with the hardware. Varied, withstands temperatures ranging between -15 and the + 40 degrees centigrade.

DIFFUSER MATERIAL

PMMA

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

3200 lm

IP RATING

IP20

ELECTRICAL CLASS

Tipo 2

LUMENS/W

3200 lm/39W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

OPTICS

General

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

39 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

82 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, flush mount, concealed profile and suspended

MINIMUM INSTALLATION HEIGHT

250

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053193884

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

25.2

UNITARY PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING GROSS WEIGHT

3

PRODUCT NET WEIGHT

2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053193884

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

55

PACKAGING WIDTH

725

PACKAGING LENGTH

650

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

25918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3

PACKAGING NET WEIGHT

2

PACKAGING WEIGHT UNIT

KGM