

Shallow floor box kit 8 elements 2 double sockets, 1 dual UPS and 2 plates for 2 RJ45 3M® grey Simon 500 Cima

REF. 52006407-030



BASIC INFORMATION

DESCRIPTION

Get here this kit for floor box for shallow and 8 elements with 2 double socket, 1 double UPS (uninterruptible power supplies) and 2 plates for 2 RJ45 (type of snap-fit 3M ®), finished in grey, of the Simon 500 Cima series. Of dimensions 329 x 252 x 69 millimetres. The kit includes 3 double sockets: 2 double sockets for standard current circuit and, on the other hand, 1 double socket for stable current circuit. In this case, the design, to be for shallow floors, makes it possible to install it on any type of raised or concrete floor (). In the event that it is in concrete flooring, it must be combined with the reference tray G401. Simon 500 Cima guarantees maximum protection in work stations against extreme conditions as a fire, since these parts are manufactured in various pure with halogen-free thermoplastic self-extinguishing, halogen-free. Also, acts as protection for the health, as it makes it possible to that, in these cases, the toxicity emitted is the minimum.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

ETIM CLASS

EC000024

MATERIAL

Plastic

PACKAGING CONTENTS

Kit and installation manual

REMARKS

To complete the installation of the product in concrete floors, once configured, it must be combined with a plastic tray (ref.G401). Alternatively, it may be combined with flush-mount trim cover (ref.52053204-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

No

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

FORMAT

Schuko

NUMBER OF MODULES

8 modules

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

NUMBER OF PLATES

2 voice and data plates

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of ductile plastic wire outputs

IK CLASSIFICATION

08

PLATE TYPE

Flat

NUMBER OF CLAMP-HOLDER HOLES

8

INDICATOR FUNCTION

Yes

NUMBER OF PRE-PUNCHED HOLES 55 X 20 MM

8

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for the fast terminal connection system

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

RAL

7011

COMPATIBLE WITH CONNECTORS

3M© Volition OCK, RJ25, K5e and K6

CURRENT (A)

16 A

RECESS DIMENSION (MM)

250 x 327 mm

IP RATING

IP4X

RJ45 ADAPTOR MODULE

Included in voice and data plates

LED CONSUMPTION INDICATOR (mA)

0.55

NUMBER OF SIDE ENTRANCES

8

NUMBER OF CONNECTORS

4

LINKABLE

Yes, the sockets for a single circuit are supplied linked together.

SNAP-FIT RJ45 PLATES

3M

RJ45 CONNECTORS

Not included

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

3M

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

NUMBER OF SOCKETS

3 double sockets: 2 double sockets for standard current circuit and 1 double socket for stable current circuit

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

8 elements

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

CLAW RANGE OF OPERATION (MM)

Between 11 and 48 mm

REMOVAL OF CONNECTOR

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using fastening claws on the concrete floor tray or on the raised floor tile (supplied with the floor box)

CAN BE INSTALLED IN TRAY

Plástica

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Its design for shallow floors allows it to be installed in any type of raised or concrete floor, combining the latter installation type with tray ref. G401

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053112731

PRODUCT NET WEIGHT

2.71

PACKAGING LENGTH

0

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053112731

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING NET WEIGHT

2.71

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.71

PACKAGING WIDTH

0