

Trim plate with combined electrical and voice and data/multimedia cable entry for 1 element white Simon K45

REF. K20/9



BASIC INFORMATION

DESCRIPTION

It is a trim plate, which consists of cabling input combined electrical and voice and data / multimedia of 1 element with white finish, this piece belongs to the series Simon K45. It is made of halogen-free thermoplastic, a material that provides maximum security in case of fire, as it avoids to extend the fire and which minimizes the toxicity if any smoke. The plate has dimensions of 45 x 45 x 8.5 mm and it can be installed both on the surface-mounted or to be flush mounted. This product includes 2 pre-punched sections measuring 13 mm in diameter (to insert 3x2.5mm leads) and 4 pre-punched sections measuring 6 mm in diameter (to cabling voice / data and multimedia). The pre-punched holes consist of retainers to prevent the cabling from becoming disconnected when pulled from the other end of the installation. For the cleaning of the plate, it is sufficient to use a soft and dry cloth.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Plate with combined electrical and voice and data/multimedia wiring entry

ETIM CLASS

EC000011

REMARKS

Includes 2 pre-punched sections measuring 13 mm in diameter (to insert 3x2.5mm leads) and 4 pre-punched sections measuring 6 mm in diameter (to insert voice/data and multimedia wiring). The pre-punched sections include retainers to prevent the cables from becoming disconnected when pulled from the other end of the installation.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Versions of plates that provide direct access to the wiring through 20x30 trunking and conduit or cable gland

IP RATING

IP20

NUMBER OF MODULES

Half

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

KIT AVAILABILITY

No

RAL

9003

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE PLATE

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.011

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436036673

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.22

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.22

UNITARY PACKAGING GROSS
WEIGHT

0.011

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140