

# Kit Flash 90 schuko power socket with "retractable cover", USB Type C Dock including 2x HDMI+LAN+3x USB Type A, USB charger Type C 20W and grommet (cable outlet) black Simon 400

REF. 43333301-138



## BASIC INFORMATION

### DESCRIPTION

Kit Flash 90 based on a retractable schuko power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and hide the connections when not in use. Includes a USB Type-C dock with 2 HDMI outputs for display, 1 Gigabit Ethernet port, and 3 USB Type-A connectors for keyboard, mouse, and any other connection device based on the USB Type-A connector. The kit includes a 20W USB Type-C charger and a cable outlet in a black finish. Supplied with a 20cm long patch cord terminated with a 3-pole Wieland® Gst18i male overhead quick connector with a safety anchor for easy connection and disconnection from the mains safely without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to make the die in the furniture where the product will be fixed and once done, connect it to the mains for it to be functional. It requires ordering the dock power supply separately (ref. CR6100121150201/14)

### FINISH

Black

### MATERIAL

Plastic

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

16 A

### SNAP-FIT RJ45 PLATES

Directly to the Dock

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

### IP RATING

IP20

### SNAP-FIT TYPE

Embedded in the dock

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Socket with retractable cover to avoid access of dust and small objects when are not in used

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### USB CHARACTERISTICS

Charging

### RJ45 CONNECTORS

Yes

### NOMINAL VOLTAGE (V~)

250 V~

### POWER DELIVERY USB

Yes

### CONNECTOR TYPE

Schuko

### RAL

9005

### QUICK CHARGE USB

Yes

### NUMBER OF CONTACTS

3

### RECESS DIMENSION (MM)

ø80 mm

### USB VOLTAGE (V~)

9 V~

### FORMAT

Schuko

### RJ45 ADAPTOR MODULE

Yes

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

No tools needed

### EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

### TYPE OF TERMINAL

#### CONNECTION - FUNCTION 1

Quick connector

### REMOVAL OF COVER

Only with tool

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD\*1 | Dir. 2014/30/UE EMC\*3 | Dir. 2011/65/UE RoHS + post. mod.\*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) \*1 \*13 \*12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016\*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012\*2 | IEC 60884-1 Ed.3.2\*1 | BS 1363-2:2016+A1:2018\*2 | UNE 20315-1-1:2017\*5 | BS 1363-4:2016+A1:2018\*2 | UNE 20315-1-2:2017\*5 | DS 60884-2-D1:2023\*4 | CEI 23-50 V4\*7 | SANS 164-1:2021\*6 | SN 441011-2-1:2019\*9 | SI 32 Fig. 204 B\*8 | AS/NZS 3112:2017\*11 | EN 50173-1:2018\*10 | EN 50563:2011 + A1:2013\*13 \*12 | EN 55032:2015 + A11:2020 + A1:2020\*12\*14 \*16 | EN 62368-1: 2014 + A11:2017\*13 \*12 | EN 55035:2017 + A11:2020\*12\*14 \*16 | ETSI-EN 301489-34 V2.1.1\*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024\*12 \*16 | EN IEC 60670-1:2021+ A11:2021\*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 \*12 \*16 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053397893

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.211

### PRODUCT NET WEIGHT

0.192

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053397893

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

120

### PACKAGING WIDTH

130

### PACKAGING LENGTH

252

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3931200

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.793

### PACKAGING NET WEIGHT

0.192

### PACKAGING WEIGHT UNIT

KGM