

Double-pole switch 16AX 250V~ with built-in pilot light and screw terminal connection system aluminium Simon 31

REF. 31134-33



BASIC INFORMATION

DESCRIPTION

Functionality and design come together in the double-pole switch with pilot light of the collection Simon 31 to give style to any room in a modern of simple lines and finishes in a stylish tone aluminium. With a dimension of 64 x 65 mm, this switch with tilting operation, it fits perfectly into all types of spaces compact guaranteeing maximum functionality and innovation. Compatible with a voltage of power of 250 Volts, and 16 AX of intensity, it is designed for installation with screw terminal connection, and supports a wire section from 0.2 to 0.5 mm and stripping of the 13 mm It is made of metal components with halogen-free insulation and trim of metallized thermoplastic, to protect the room in case of fire. Thanks to these materials, it can reach a temperature range of 5 to 40 ° C with maximum temperatures of -25 to 50 °C.

FINISH

Aluminium

COMPATIBILITY

Simon 31 frames

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Can be combined with article 31803-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 AX

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

INDICATOR FUNCTION

Yes

TYPE OF MECHANISM

Pivoting

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.095

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1.518

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053071748

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.475

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.475

UNITARY PACKAGING GROSS
WEIGHT

0.095

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223

MECANISMOS SIMON 31, 75, 77, 82 Y 88

Mecanismos básicos / Basic switches



Interrupor unipolar / Single-pole switch
XXXX101-XXX



Interrupor unipolar / Single-pole switch
7700101-039



Pulsador / Push button switch
XXXX150-XXX



Pulsador / Push button switch
7700150-039



Interrupor bipolar / Double pole switch
XXXX133-XXX



Conmutador / 2-way switch
XXXX201-XXX



Conmutador / 2-way switch
7700201-039



Conmutador cruce / Intermediate switch
XXXX251-XXX



Conmutador cruce / Intermediate switch
7700251-039



Grupo 2 interruptores / 2 switches group
XXXX398-XXX



Pulsador desconexión / Push button disconnection switch
XXXX152-XXX



Grupo dos conmutadores / 2-way switches group
XXXX397-XXX



Grupo de pulsadores desconexión / Push button switch
desconexion group XXXX395-XXX



Grupo conmutador y pulsador / 2-way and push button switch group
XXXX301-XXX



Interrupor unipolar / Single-pole switch
XXXX102-XXX



Interrupor con piloto / Push button pilot switch
7700112-039



Interrupor bipolar / Double pole switch
XXXX134-XXX



Conmutador / 2-way switch
XXXX202-XXX



Interrupor unipolar con luminoso / Single-pole switch with light
XXXX104-XXX



Pulsador con luminoso / Push button switch with light
XXXX160-XXX



Pulsador con luminoso / Push button switch with light
7700160-039



Conmutador con luminoso / 2-way switch with light
XXXX204-XXX



Conmutador cruce con luminoso / Intermediate switch with light
XXXX254-XXX