

POINT 56 Spotlight Mini Rail 4000 K Wide Flood DALI Black

REF. 92061313-488



BASIC INFORMATION

BODY MATERIAL

Aluminium injection moulding

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic, Office, Retail, Hotel, Contract

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

COLOR TYPE

CW

IP RATING

IP20

DIRECTIONAL

Yes

LIGHTING EFFICIENCY (LM/W)

hasta 79 lm/W

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DRIVER INCLUDED

Yes

LUMENS (LM)

1085 lm

POWER SUPPLY (V~)

220/240 V~

ELECTRICAL CLASS

II

NUMBER OF LUMINAIRES

1

RAL

9005

ENERGY EFFICIENCY

A+

MACADAM STEPS

<3 Step MacAdam

COLOR TEMPERATURE (K)

4000 K

L70 (°C)

150000h at 25°C

OPTICS

Wide Flood 46°

CONTROL

DALI

L90 (°C)

40000h at 25°C

POWER (W)

14 W

CHROMATICS CRI ICONS

CRI
90

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Rail

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547052523

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547052523

PACKAGING VOLUME

4452120

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

83

PACKAGING GROSS WEIGHT

0.44

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

180

PACKAGING NET WEIGHT

0.4

UNITARY PACKAGING GROSS WEIGHT

0.58

PACKAGING LENGTH

298

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.4