

Front kit for 3 elements with 2 German socket outlets and 1 2xUSB charger gloss white Simon 100

REF. 10020308-130



BASIC INFORMATION

DESCRIPTION

This front kit for 3 elements, with 2 Schuko plug bases (16 A) and with a double series USB charger has the following reference: 10020308-130 and an elegant glossy white finish. Its installation is very simple: it can be placed horizontally and vertically.

The type of emborning is by cut (1 click system) and for the USB part, by screw-type. The type of activation is by insertion and has dimensions of 225.5x83.5mm. This product is part of the Simon 100 range, so it is compatible with all the mechanisms in this series.

For proper maintenance and operation, it must be preserved in a temperature range of 5 to 40° C and a storage temperature range of -25 to 50° C.

This is a device that has been made based on the regulations: directive 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950-1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3 + ETSI-EN 301489-34 v14 .1 * 3 + IEC 60884-1 Ed. 3.2 * 1 and is marketed in the EC.

FINISH

Gloss white

COMPATIBILITY

Kit mechanisms Simon 100

ETIM CLASS

EC000007

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism and instructions

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

3 elements

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko,USB

MONOBLOCK

Yes

VERSION

3 elements

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical and horizontal

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053201589

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053201589

PACKAGING VOLUME

480295.2

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

226

PACKAGING NET WEIGHT

0.13

UNITARY PACKAGING GROSS
WEIGHT

0.13

PACKAGING LENGTH

84

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.13