

MD-23x6 Hallway PIR+LUX SR recessed DALI-2 Master round white IP20

REF. 89205415-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 5 m. It has a detection angle of 360° and an opening angle of 45°. The tangential detection range is 23 x 6 m and the radial detection range is 12 x 6 m. The light regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The configuration of the detector is done through potentiometers and remote control. It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Master. The number of dimmable luminaires through the DALI bus is 30 (1 group). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. White finish, protection rating IP 20, and dimensions: Ø 124 x 121 mm. 5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH
White

**COMPATIBLE WITH MECHANICAL
PUSH BUTTON**
No

ETIM CLASS
EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP20

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341926

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.304

PRODUCT NET WEIGHT

0.196

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341926

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

141

PACKAGING WIDTH

141

PACKAGING LENGTH

141

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2803221

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.304

PACKAGING NET WEIGHT

0.196

PACKAGING WEIGHT UNIT

KGM