

Downlight 800.23 Black 24W 3000K

REF. 80023038-683



BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

2400 lm/24W

IP RATING

IP54

ELECTRICAL CLASS

tipo 2

OPTICS

Extensive

OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

L70 (°C)

50.000 h a 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

POWER SUPPLY (V~)

220/240 V~

LIGHT BEAM APERTURE ANGLE (°)

60°

POWER (W)

24W

COLOR TEMPERATURE (K)

4000K

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

105 lm/W

COS Φ

0.95

LUMENS (LM)

2400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

115

INSTALLATION TYPE

Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS
WEIGHT
0.974

PRODUCT NET WEIGHT
0.974

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053308011

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
145

PACKAGING WIDTH
250

PACKAGING LENGTH
215

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
7793750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.192

PACKAGING NET WEIGHT
0.974

PACKAGING WEIGHT UNIT
KGM