

**Two-pole socket outlet 10A 250V~ for half element with
safety device and screw terminal connection ivory Simon
27 Play**

REF. 27431-61



BASIC INFORMATION

DESCRIPTION

The security has been a maxim of Simon to the throughout his 100 years of history creating elements for electrical and electronic systems. In the sockets category, we have the Socket-outlet two-pole 16 A 250V~ of half an element and screw-terminal connection in ivory finish of the Simon 27 Play series, it includes a safety device that makes it perfect for rooms with minors in which we want to avoid any type of unexpected accident or in buildings with children such as educational centres or hospitals. It is ideal to assemble in new work or to replace in reforms carried out in certain rooms of a home or a company, being apt for replacement or export. The metal components with halogen-free thermoplastic insulation and thermoplastic trim with which it has been manufactured stand out for their durability and resistance.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

Suitable for replacement or export.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Two-pole

TYPE OF MECHANISM

Insertion

VERSION

Single

INDICATOR FUNCTION

No

MONOBLOCK

No

VOLTAGE (V~)

250 V~

CURRENT (A)

10 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252048

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.033

PRODUCT NET WEIGHT

0.033

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053038079

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

52

PACKAGING WIDTH

105

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1201200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.665

PACKAGING NET WEIGHT

0.66

PACKAGING WEIGHT UNIT

KGM