

Multisensor True Presence HF+LUX recessed box KNX white IP20

REF. 89220724-230



BASIC INFORMATION

DESCRIPTION

Multisensor of real presence and brightness for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 12 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 15 m and the radial detection range is 15 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 30 s - 1092 min. The configuration of the detector is done through the bluetooth and KNX application.

It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 40 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: 0 - 40 °C.

White finish, protection grade IP 20 and dimensions: 123 x 123 x 33 mm.

5 years warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION
HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356753

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

UNITARY PACKAGING GROSS
WEIGHT

0.27

PRODUCT NET WEIGHT

0.156

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING EAN

8421053356753

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

162

PACKAGING WIDTH

100

PACKAGING LENGTH

143

PACKAGING MEASUREMENT
UNIT

MMT

PACKAGING VOLUME

2316600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.27

PACKAGING NET WEIGHT

0.156

PACKAGING WEIGHT UNIT

KGM