Double element access cover for installation on pavement or technical floor graphite Simon Cima

REF. **S100/14**



BASIC INFORMATION

FINISH
Graphite

MATERIAL
Various

COMPATIBILITY
With plastic buckets of 1 double element Simon Cima when installed on floor pavement.

ETIM CLASS
EC001903

TECHNICAL INFORMATION

HEAT RESISTANCE (ºC)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
7021

RECESS DIMENSION (MM)
170 x 115 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (ºC)
+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

CAN BE INSTALLED IN TRAY
Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436020085

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
2871375

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.55

PRODUCT NET WEIGHT
0.55

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436020085

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
95

PACKAGING WIDTH
155

PACKAGING LENGTH
195

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2871375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.55

PACKAGING NET WEIGHT
0.55

PACKAGING WEIGHT UNIT
KGM