

Projector 889 200W 3000K

REF. 88935038-883



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for shop window and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in different power options, the outdoor projector 889 allows for selecting the appropriate model based on the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 3000K. Power: 200W. Lumens: 18000lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 406 mm x 333 mm x 47 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

90 lm/W

LUMENS (LM)

18000 lm

OPTICS

Symmetric

POWER (W)

200 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440339

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.394

PRODUCT NET WEIGHT

2.29

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440339

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

350

PACKAGING WIDTH

125

PACKAGING LENGTH

430

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

18812500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

4.788

PACKAGING NET WEIGHT

2.29

PACKAGING WEIGHT UNIT

KGM