Trim plate with voltage indicator for 1 element white Simon K45

REF. **KL05/9**



BASIC INFORMATION

DESCRIPTION

Trim plate with voltage indicator of 1 element, finished in graphite colour and belonging to the series Simon K45. This plate is ideal for installation in surface-mounted and is recessed and in public places with a temperature between 5 and 60 ° C, approximately, although it ' s true that is able to withstand temperatures. Complies with the regulation European UNE-EN 61.000-3-3: 2009 and is manufactured with metal components. It measures 45 x 45 mm and to clean it, just have to wipe it with a soft and dry cloth, without resorting to use any cloth or abrasive cleaner containing chlorine. The series Simon K45 offers flat plates and plates to facilitate the workplace solutions, thus offering you a complete solution and contrasted quality. All the plates belonging to the series Simon K45 support any connector of the market and also are plates with dust cover of closure automatic, helping to keep inalterables the transmission parameters and also have a Labelling area or for pasting of the identification label.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Plate with voltage indicator and installation manual

ETIM CLASS

EC000011

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

INDICATOR FUNCTION
Yes

IP RATING
IP20

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

RAL
9003

VERSION
Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING
Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
UNE-EN 61.000-3-3:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.036

PRODUCT NET WEIGHT
0.036

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436035522

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
88

PACKAGING WIDTH
123

PACKAGING LENGTH
136

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1472064

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.37

PACKAGING NET WEIGHT
0.36

PACKAGING WEIGHT UNIT
KGM