

Monoblock floor trunking 2.75m and 85x18mm with 2 compartments

REF. TF21172/8



BASIC INFORMATION

DESCRIPTION

The monoblock DCS TF21172/8 floor trunking is the perfect solution for indoor cable distribution where security and durability are top priorities. With an 85x18 mm profile, it is made of high-quality anodized aluminum, ensuring IK10-grade mechanical protection against impacts and external aggressions. Its maximum load capacity of 65 kg/cm² makes it ideal for offices, warehouses, and workshops. Additionally, the closed monoblock design provides enhanced security, keeping cables inaccessible once installed.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION

10

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

65 Kg/cm2

MONOBLOCK

Yes

RAL

7035

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

0.891

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436035614

UNITS CONTAINED PACKAGING

11

PACKAGING HEIGHT

150

PACKAGING WIDTH

110

PACKAGING LENGTH

3040

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

50160000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

9.801

PACKAGING NET WEIGHT

9.801

PACKAGING WEIGHT UNIT

KGM