

ARCH Downlight X-Less connection Accessory Network

REF. 91592019-000



BASIC INFORMATION

APPLICATION

Domestic, Office, Retail, Hotel, Contract Unit

PACKAGING CONTENTS

Unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LIGHTING EFFICIENCY (LM/W)

111 lm/W

IP RATING

IP20 / IP43

DRIVER INCLUDED

No

PHOTOBIOLOGICAL CLASSIFICATION

Class II

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

II

POWER FACTOR (Φ)

> 0,9

POWER SUPPLY (V~)

110/240 V~

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted, Surface-mounted

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053219942

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053219942

PACKAGING VOLUME

125000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.15

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

50

PACKAGING NET WEIGHT

0.03

UNITARY PACKAGING GROSS
WEIGHT

0.15

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.03