

Brightness sensor surface DALI-2 Input squared white IP54

REF. 89262330-230



BASIC INFORMATION

DESCRIPTION

Square surface light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. The light regulation range is 2 - 1000 lux. The detector configuration is done via DALI. It has a TEACH operating mode. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 6 mA. The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, IP 54 protection grade, and dimensions: 95 x 95 x 42 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000189

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9003

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401590

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.227

PRODUCT NET WEIGHT

0.138

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053401590

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.227

PACKAGING NET WEIGHT

0.138

PACKAGING WEIGHT UNIT

KGM