

Socket 16A 250V ~ with connection system 1click® Simon 100

REF. 10000458-039



BASIC INFORMATION

COMPATIBILITY

Frames Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET	INDICATOR FUNCTION	NOMINAL VOLTAGE (V~)
CE	No	250 V~
CABLE SECTION ADMITTED (MM)	CURRENT (A)	OPERATING TEMPERATURE RANGE (°C)
From 1,5 to 2,5 mm	16 A	0 - 40 °C
NUMBER OF POSSIBLE ELEMENTS	IP RATING	STORAGE TEMPERATURE RANGE (°C)
1 element	IP20	-25 - 75 °C
FORMAT	TYPE OF MECHANISM	VERSION
French	Insertion	Unique
	MONOBLOCK	
	No	

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX	INSTALLATION TYPE
13	universal	Suitable for flush mounting
CLAW	INSTALLATION DIRECTION	TYPE OF TERMINAL CONNECTION - FUNCTION 1
	Horizontal, Vertical	1 click connection (1 click®)

REGULATIONS

REGULATIONS

EN 50581:2012 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053142097

PACKAGING VOLUME
1584375

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
65

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.045

PACKAGING WIDTH
125

PACKAGING NET WEIGHT
0.46

PRODUCT NET WEIGHT
0.046

PACKAGING LENGTH
195

PACKAGING WEIGHT UNIT
KGM

