# Satellite socket single F type female with trim plate black Simon K45

REF. **K102C/14**



# BASIC INFORMATION

## DESCRIPTION

In an original finishes in black, the simple F type female satellite socket with trim plate and insertion by welding and form part of our collection Simon K45 and is suitable both for surface and flush mounting, has dimensions of 22.5x45 mm, a thickness of 42,9 mm and is made of metal materials with thermoplastic insulation self-extinguishing halogen-free in order to ensure that is no flame spread in case of fire, along with a very low toxicity in the event of smoke generation. There are some important as data to be taken into account, we inform you that the maximum recommended length of cabling is 90 metres. If you are in which they were looking for the latest in technology for your home, you are of congratulations, as the series Simon K45 has been specially designed to satisfy the desires of the most demanding, and that is that our I wish to innovate and improve we put as one of the brand in the sector. So that you the games and confident in our specialists.

## FINISH

Black

## COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

## PACKAGING CONTENTS

Simple F type female satellite socket

## ETIM CLASS

EC000439

## REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### CABLE SECTION ADMITTED (MM)
From 6 to 8 mm

### CONNECTOR TYPE
SAT

### NUMBER OF CONTACTS
1

### NUMBER OF POSSIBLE ELEMENTS
1/2 element

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

### RAL
7021

### STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

### VERSION
Single

### NUMBER OF WIRES
1

## INSTALLATION AND MAINTENANCE

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

### INSTALLATION TYPE
Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS
Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 + A1:2015 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
91140

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.014

PRODUCT NET WEIGHT
0.014

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436046535

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.14

PACKAGING NET WEIGHT
0.14

PACKAGING WEIGHT UNIT
KGM