Double Schuko socket outlet 16A 250V~ with safety device and quick terminal connection white K45

REF. **K12/9**



BASIC INFORMATION

FINISH
White

MATERIAL
Plastic

COMPATIBILITY
Simon K45 enclosures for installation on wall, floor, ceiling, and furniture, and Simon 500 Cima enclosures (requires combining with the adapter from K45 to 500 Cima ref. 50012088-030).

ETIM CLASS
EC000125

TECHNICAL INFORMATION

FORMAT
Schuko

IP RATING
IP20

NOMINAL VOLTAGE (V~)
250 V~

CURRENT (A)
16 A

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
9003

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
12

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod.|EN IEC 63000:2018|IEC 60884-1 Ed. 3.2|UNE 20315-1-1:2017|UNE 20315-1-2:2017|DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053354810

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.093

PRODUCT NET WEIGHT
0.085

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053311608

UNITS CONTAINED PACKAGING
6

PACKAGING HEIGHT
60

PACKAGING WIDTH
145

PACKAGING LENGTH
190

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1653000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.558

PACKAGING NET WEIGHT
0.51

PACKAGING WEIGHT UNIT
KGM