

Push-button switch with light symbol 10A 250V~ and fast terminal connection system ivory Simon 31

REF. 31651-31



BASIC INFORMATION

DESCRIPTION

Push-button switch of the Simon 31 series with light engraving and quick terminal connection. It has a current of 10A and 250V. The finish of this control mechanism of the brand is ivory in colour, it has a rocker operation. In total, there are five finishes available for the push buttons of the Simon 31 series. For this reason, it is recommended to choose the frame in the same tone as the rocker that has been installed. In this case would have to install the frame in ivory finish. The push-button switch measures 64 x 65 millimetres and this is the individual version of two modules and a single element. The wire section admitted is from 1.5 to 2.5 millimetres and the stripping of wire necessary is 11 millimetres. It can withstand a humidity of 95% RH, but without dew. It is made of metal components with thermoplastic, isolated halogen-free. This type of materials guarantees maximum security, because they support extreme temperatures (between -25 to + 50 degrees centigrade).

FINISH

Ivory

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Available in 5 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053007365

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

83

PACKAGING GROSS WEIGHT

0.9

UNITARY PACKAGING GROSS WEIGHT

0.09

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

0.9

PRODUCT NET WEIGHT

0.09

PACKAGING LENGTH

221

PACKAGING WEIGHT UNIT

KGM