

Spotlight 640.00 Rail WW CRI92 Wide Flood White

REF. 64000030-493



BASIC INFORMATION

DESCRIPTION

Simon, through the line of 640 spotlights, both of rail and recess, exceeds all the features based on LED technology aimed at the applications of surface lighting. LED technology guarantees the lighting performance of the product, which are the most sought after by professionals of design and the installations, this is the faithful reproduction of colours and light intensity, over time. No emission of UV and IR radiation, makes it ideal for illuminating heat-sensitive products and prevents the degradation of colours. The colour temperatures of also allows you to select the most suitable hue of light over to the products that you want to highlight. It is available in versions for rail (Spotlight 640.00) with Spot and Wide Flood optics and recessed (Spotlight 640.20) with Wall Washer optics. This is of a spotlight indoor lighting. For position, place in 3-phase rail provided separately. Spotlight 640 Rail. The temperature of the colour 3000 K WW. WIDE FLOOD optics, which allows the position, place an emphasis on which we wish to illuminate. Colour White. Category B spotlights line 640. Durability 30,000 h at 25 ° C. 120-240 V 50 / 60 Hz. Switching on ON-OFF. Temperature cross-section 35 ° C maximum. Weight 1.4 kg Placing in Rail 3-phase rail. Dimensions 100x102 mm

APPLICATION

Accent lighting, General lighting

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

2100 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2100 lm/30W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

ELECTRICAL CLASS

Type 1

OPTICS

Wide Flood

POWER SUPPLY (V~)

120/240 V~

L70 (°C)

100,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

30 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

50.000 h

CRI

92

LIGHTING EFFICIENCY (LM/W)

70 lm/W

CHROMATICS CRI ICONS

CRI
92

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase rail

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.574

PRODUCT NET WEIGHT

1.372

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053133279

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

230

PACKAGING WIDTH

130

PACKAGING LENGTH

180

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5382000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.372

PACKAGING WEIGHT UNIT

KGM