Kit Flash 90 consisting of swiss modular power socket, USB charger Type C 20W and RJ45 female-female data connector category 6 UTP black Simon K45

REF. **KR3380023/14**



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular swiss power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and conceal the connections when not in use. Includes a 20W USB Type-C charger and a Category 6 UTP RJ45 data connector in black finish. Supplied with a 20cm long patch cable terminated with a 3-pole Wieland® Gst18i male aerial quick connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. All that is required is to cut the hole in the furniture where the product will be mounted. Once this is done, connect it to the mains power supply for operation.

FINISH	MATERIAL	ETIM CLASS
Black	Plastic	EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Protective lid available (as an option) to protect the connections against entry of dust and small objects

RJ45 CONNECTORS
Yes

CONNECTOR TYPE
Swiss

NUMBER OF CONTACTS
3

DUST SHUTTER
No

FORMAT
Swiss

CURRENT (A)
10 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
250 V~

RAL
9005

RECESS DIMENSION (MM)
ø80 mm

RJ45 ADAPTOR MODULE
Yes

SNAP-FIT RJ45 PLATES
Directly to the trim cover

SNAP-FIT TYPE
Keystone

USB CHARACTERISTICS
Charging

USB CURRENT (A)
2,2 A

POWER DELIVERY USB
Yes

QUICK CHARGE USB
Yes

USB VOLTAGE (V~)
9 V~

VOLTAGE (V~)
250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
No tools needed

REMOVAL OF COVER
Only with tool

EXTINGUISHING (ºC)
+650 ºC (according to standard IEC 60670)

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 |Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053398456

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.757

PRODUCT NET WEIGHT
0.597

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053398456

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
120

PACKAGING WIDTH
130

PACKAGING LENGTH
252

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3931200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.757

PACKAGING NET WEIGHT
0.597

PACKAGING WEIGHT UNIT
KGM