

ARCH Downlight X-Less connection Accessory Network

REF. 91592019-000



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Hotel,Contract Unit

PACKAGING CONTENTS

Unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LIGHTING EFFICIENCY (LM/W)

111 lm/W

IP RATING

IP20 / IP43

DRIVER INCLUDED

No

PHOTOBIOLOGICAL CLASSIFICATION

Class II

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

II

POWER FACTOR (Φ)

> 0,9

POWER SUPPLY (V~)

110/240 V~

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted, Surface-mounted

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053219942

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.03

PRODUCT NET WEIGHT

0.03

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053219942

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

50

PACKAGING WIDTH

50

PACKAGING LENGTH

50

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

125000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.03

PACKAGING NET WEIGHT

0.03

PACKAGING WEIGHT UNIT

KGM